

Stand-Assist Lift

HCPCS:



FIGURE A



FIGURE B



FIGURE C



FIGURE D




FIGURE E

- Provides stable assistance in standing, transferring and toileting
- Four sling attachment points enable the lift to accommodate a variety of stand-up sling designs
- Extra-wide, non-skid foot plate provides a stable base for foot positioning (Figure A)
- Soft, padded adjustable leg support includes a support strap to secure legs to the support (Figure A)
- Easy-roll 4" casters mean stability and easy maneuverability over a variety of surfaces (Figure B)
- 4.5" under-bed clearance provides access under most long term care beds
- 24V DC motor provides power and reliability
- Motor has an emergency stop button and manual lowering feature
- Fast charging, rechargeable battery is removable to eliminate lift downtime
- Battery has a charged and low-charge indicator Audible tone when charge is complete
- Battery charge meter indicates the battery power status while in use
- Audible tone when battery power is below 50%
- Includes removable, rechargeable battery item #13240BATT (Figure C), charging station #13255 (Figure D) and wall-mount bracket item #13260 (Figure E)

PRODUCTS	Description
13246	Stand-Assist Lift, BX

SPECIFICATIONS	Description
Base Clearance	4.5"
Base Width	40" (Open) 24.5" (Closed)
Boom Height	26" - 81"
Carton Shipping Weight	128 lbs.
Casters	3" (Front) 4" (Rear)
Weight	113 lbs.
Weight Capacity	400 lbs

PARTS	Description
13240BATT	BattPackw/Batteries,13240,13244,13246,1/, EA
13260	Battery&ChargerBracket,Elec Patient,1/ea, EA
13255	External Charger w/out PowerCord,1/ea, EA