

The Stature® patient lift, Hoyer®'s flagship product, recognizes the true needs of the modern care environment. With a safe working load of 500 lbs and one of the largest lifting ranges available (min 26.6" max 77.7"), the Stature is able to cope with even the most demanding and technical of resident handling situations.

The Stature can lift residents from the floor as well as accommodate transfers to higher surfaces, while allowing the choice of different sling systems. Careful attention to product design ensures correct ergonomic usage, protecting both the resident and caregiver from injury at all times.



Smart Monitor



The unique Smart Monitor control box is programmable and will accurately record and display vital lift utilization and service data. An easy to read LCD display provides the valuable information at the touch of a button.



Power Positioning Cradle

Powered positioning enhances caregiver safety while maintaining resident comfort. Compact, removable design promotes ease of service, without removing entire lift from service.



Integrated Hand Control

Allows caregiver to remain close to the resident during the repositioning process.



Scale

Integrated design allows caregiver to adjust position of display for easier viewing. Simple, intuitive controls provide resident's weight in pounds or kilograms.

SPECIFICATION	IMPERIAL	METRIC
Safe Working Load	500 lbs	227 kg
Maximum Overall Length	54.7"	1390 mm
Minimum Overall Length	50.8"	1290 mm
Maximum Overall Height	83.8"	2130 mm
Minimum Overall Height	76.6"	1945 mm
Maximum Height to Attachment Point (4 pt)	61.0"	1550 mm
Minimum Height to Attachment Point (4 pt)	15.4"	390 mm
Maximum Height to Attachment Point (6 pt)	77.1"	1975 mm
Minimum Height to Attachment Point (6 pt)	26.6"	675 mm
Turning Radius	61.0"	1550 mm
Legs Open - External Width	53.5"	1360 mm
Legs Open - Internal Width	48.4"	1230 mm
Legs Closed - External Width	29.9"	760 mm
Legs Closed - Internal Width	25.1"	640 mm
Overall Height of Legs	4.3"	110 mm
Ground Clearance	1.2"	30 mm
Front Twin Casters	4.0"	100 mm
Rear Braked Casters	4.0"	100 mm

WEIGHTS	IMPERIAL	METRIC
Mast, Base & Boom Assembly	142 lbs	64.5 kg
4 Point Positioning Cradle	13.2 lbs	6.0 kg
Power Pack	6.6 lbs	3.0 kg
Total	162 lbs	73.5 kg

ELECTRIC SHOCK PROTECTION

Charger – Class II
Lift – Internal power source

DEGREE OF SHOCK PROTECTION

Charger – Type B
Lift – Type B
Intended operating environment: >+5°C <+40°C
Outside this environment functionality and safety may be compromised

ELECTRICAL SPECIFICATIONS

Battery – 24vDC rechargeable sealed lead acid type
Battery capacity – 3.2A Ampere hours
Charger rated input – 100-240V AC 24 VDC 50/60Hz
Charger rated output – 29.5 VDC, Max. 19 W